

FEATURE UPDATE | DECEMBER 2018

Version 183 Firmware Update

Version 183 firmware is now available on DMPDealerAdmin.com or for download at DMP.com/Dealer_Direct.

Effective January 21st, 2019, all XR Series panels will be manufactured with Version 183 firmware. The following features are available:

Features

⊕ Multiple Card Formats

With Version 183, you can now program a new 734 or 734N/734N-POE with up to seven different card formats in addition to DMP format. Card formats can be programmed in **Device Setup** in Panel Programming.

The 734 Wiegand Interface Module validates credentials by total bit length; if a card is presented and there's a matching programmed card format, the card is processed in that programmed format. If there is not a matching card format for the bit length, it's processed in the DMP format. Once the card formats are set up, that data is copied and can be remotely sent to each device, such as keypads. You can program multiple card formats from Dealer Admin and Remote Link.

⊕ Carbon Monoxide (CO) Zone Type and Temporal 4 Bell Cadence

With Version 183, carbon monoxide detectors have a designated Carbon Monoxide (CO) zone type in **Zone Information**. For a CO Zone Type, the default bell cadence is **Temporal 4**, which can be programmed in **Bell Options**.

⊕ 738T Support for XR150/XR550

With Version 183, XR150/XR550 now support the 738T. This allows you to take over Honeywell, Interlogix, or 2GIG wireless transmitters without replacing the wireless sensors. The 738T should be wired to the keypad bus of XR Series panels and cannot be used on an LX Bus. The XR150 can support up to 2 738T's, while the XR550 can support up to 4 738T's.

⊕ New Door Propped Push Notifications

If Door Propped is enabled for a zone on a panel with Version 183, a push notification will be sent to the users mobile device.

Supporting Software Updates

- Dealer Admin Version 2.15.2 - Dealer Admin now supports multiple card formats, the new CO Zone Type and Temporal 4 bell cadence, as well as wireless encryption.
- Remote Link Version 1.88 - Remote Link Version 1.88 now supports multiple card formats, the new CO Zone Type and Temporal 4 bell cadence, as well as wireless encryption. The update is available for free at DMP.com/Dealer_Direct.

Obtaining the New and Firmware

XR Series firmware updates are available, free of charge, at DMPDealerAdmin.com or DMP.com/Dealer_Direct.