



V-6000 Series Cameras



BENEFITS

- PoE and Wi-Fi bullet, turret, dome and cube cameras
- Allows commercial users to observe employee activities, monitor areas or entrances
- Video verification available via Virtual Keypad app and the monitoring center automation software
- Your customers can view live video and events via Virtual Keypad
- Exclusive EASYconnectVPN™ for encrypted connectivity
- NDAA Compliant

THE POWER OF VIDEO

Video cameras continue to be a crucial part of any intrusion system. DMP's new line of video cameras include additional options and features to provide your customers with greater peace of mind.

- ▶ New camera formats include 2.4 GHz Wi-Fi and hardwired cube, bullets, domes and turrets
- ▶ Hardwired cameras incorporate video analytics, including line crossing, person or vehicle detection
- ▶ Easily add cameras to new and existing systems

EASYCONNECTVPN™

A virtual private network (VPN) is one of the most essential tools for your customers to protect their businesses and homes, ensuring that video sent to SecureCom Wireless servers via the Internet remains private.

- ▶ Encapsulates and encrypts traffic before it is sent over the Internet
- ▶ Private firmware exclusively for SecureCom and DMP
- ▶ Standard protocol for cameras and NVR's

VIRTUAL KEYPAD™

Virtual Keypad enables your customers to manage their video clips, including:

- ▶ View live video
- ▶ View events
- ▶ Export/Save
- ▶ Filter by event type



VIDEO VERIFICATION

DMP's Video Verification feature provides the added benefit of visual information that is sent with alarm notifications to a monitoring station.

- ▶ Your monitoring center and customers can quickly verify if an alarm is real or false
- ▶ Eliminates fines incurred for police dispatches to false alarms
- ▶ Faster police response due to professional verified alarms



Models:	V-6012B 2MP Bullet	V-6012WB 2MP Bullet with Wi-Fi	V-6014B 4MP Bullet	V-6022WC 2MP Cube with Wi-Fi	V-6042T 2MP Turret	V-6044T 4MP Turret	V-6052WD 2MP Dome with Wi-Fi
Analytics	Line Crossing, Person or Vehicle	Motion Events	Line Crossing, Person or Vehicle	Motion Events	Line Crossing, Person or Vehicle		Motion Events
Resolution	2.0 megapixel	2.0 megapixel	4.0 megapixel	2.0 megapixel	2.0 megapixel	4.0 megapixel	2.0 megapixel
Power	12V			5V	12V		12V
Weight	0.93lb	0.55 lb	0.93lb	0.31lb	0.93lb		0.71 lb
Dimensions	6.1" x 2.5" x 2.5"	6.8" x 3" x 2.8"	6.1" x 2.5" x 2.5"	3.0" x 1.7" x 4.9"	4.4" x 3.7"		4.29" x 3.3"
Operating Temp	-22°F - 140°F			14°F - 104°F	-22°F - 140°F		-22°F - 140°F
IR Distance	131 Feet (40M)	98 Feet (30M)	131 Feet (40M)	32 Feet (10M)	98 Feet (30M)		98 Feet (30M)
Lens	2.8MM			2.8MM	2.8MM		2.8MM
FOV	106°H x 57°V x 115°D	101°H x 55°V x 111°D	106°H x 57°V x 115°D	110°H	106°H x 57°V x 115°D		101°H x 55°V x 111°D
Accessories	V-6010-JB Junction Box V-SD64G 64 GB SD card V-12V-PS 12V 2A Plug-In Power Supply			V-SD64G 64 GB SD card	V-6040-TP Transfer Plate V-6040-JB Junction Box V-SD64G 64 GB SD card V-12V-PS 12V 2A Plug-In Power Supply		V-6040-TP Transfer Plate V-6040-JB Junction Box V-SD64G 64 GB SD card V-12V-PS 12V 2A Plug-In Power Supply

V-6010-JB Junction Box



V-6040-JB Junction Box



V-6040-TP Transfer Plate

