


1165/1165H/1165HS Wireless Commercial Smoke Detectors

Description:
The Model 1165 Smoke Detector, 1165H Smoke/Heat Detector, and 1165HS Smoke/Heat Detector with Sounder are wireless detectors used with the 1100X Series Wireless Receivers.




Specifications

Battery
Life Expectancy At least 1 year
(normal operation)
3.0V Lithium Panasonic CR123A or
DMP CR123-Fire
See Battery Life Expectancy for full details.
Low battery
Threshold signal 2.70V
Beep rate 1 every 30 sec. ± 2 sec.
Sounder pattern
Temporal 85dBa at 10'
Sensitivity 2.3% ±0.8%
Frequency Range 903 - 927 MHz

Dimensions
Detector 5.6" x 2.4"
(14.3cm x 6.1cm)
Base 5.4" x 0.46"
(13.7cm x 0.46cm)
Heat alarm specifications:
Rate-of-rise 15°F/min > 105°F
(8.3°C/min > 40.6°C)
Fixed 135°F ± 5°F
(57.2°C ± 2.8°C)
Drift compensation
adjustment 0.5%/ft. max.
Color White

Listings and Approvals
FCC Part 15 Registration ID CCKPC0088
IC Registration ID 5251A-PC0088
Underwriters Laboratories (UL) Listed
ANSI/UL 268 Smoke-Automatic Fire Detectors

Architects and Engineers CAD Drawings		 Digital Monitoring Products 2841 E. Industrial, Springfield, MO 65802	
FILE NAME		TITLE	
DRAWN LK	DATE 09-09-09	1165 Series Commercial Wireless Smoke Detector	
CHECKED	SCALE NTS	PART NO.	REV.
APPR'VD	SHEET 1 OF 1		