



veryone knows the story about the boy who cried wolf. Unfortunately, the moral of that fable has real world applications. These days, security system false alarms are a growing concern. In an effort to achieve False Alarm Reduction (FAR), Security Command is offering the XR series of security system control panels.

The XR series provides more usable false alarm reduction features than any other burglary/fire control panel on the market. These control panels reduce false alarms by employing a self-verification system, which double-checks an alarm before it is sent to your alarm company. A similar feature, called Fire Verification, double-checks smoke detectors before sending an alarm.

The Security Command XR system rings a bell to alert you if a door is left open when turning on the alarm system. In addition, the system compensates for the mistakes that people make by permitting you to cancel alarm reports or delay transmission to provide you time to disarm the system. Finally, you have the flexibility to customize all of these powerful false alarm reduction features.

So don't cry wolf. Make sure your call for help is heeded. Choose the Security Command XR series to ensure that your false alarms are few and FAR between.







features and benefits

- ENTRY & EXIT DELAY ANNUNCIATION
 Reminds user that system status is changing and requires action
- System Recently Armed Reporting
 Alerts Central Station personnel to likelihood of user error
- EXIT ERROR KEYPAD ALERT AND REPORTING
 Alerts Central Station that alarm occurred during Arming
- System Test by User
 Allows system diagnostics to verify system functionality and identify problems
- SWINGER ZONE BYPASSING
 Automatically removes sensor with multiple triggers from the system.
- CROSS-ZONING ZONE PROGRAMMING
 Requires sensor activation at least twice for an alarm
- TRANSMIT DELAY

 Provides the user time to cancel an active alarm before reporting to Central Station

ABORT REPORTING

Alerts Central Station that system has been disarmed by an authorized user

Unique Duress Code

Eliminates accidental false alarms from keypad entry errors

FIRE VERIFICATION

Requires sensor activation at least twice for an alarm

2-BUTTON PANIC KEYS

Prevents accidental tripping of Panic Alarm

CALL WAITING CANCEL

Call Waiting inhibits a busy signal even though a telephone line is in use. If the Central Station attempts to verify an alarm while the control panel is sending a report, the operator will hear the phone ringing--as opposed to a busy signal--believe the premises is unoccupied and dispatch the police.

FAR AND AWAY THE LEADER